

# AIRWORTHINESS DIRECTIVE

released by DIRECTION GENERALE DE L'AVIATION CIVILE

*Inspection and/or modifications described below are mandatory. No person may operate a product to which this Airworthiness Directive applies except in accordance with the requirements of this Airworthiness Directive.*

Translation of 'Consigne de Navigabilité' ref. : 75-223-3  
In case of any difficulty, reference should be made to the French original issue.

## AIRBUS INDUSTRIE

### A300 aircraft

Main landing gear barrel - Actuating cylinder attachment

AIRBUS A 300 B1, A 300 B2-1A and A 300 B2-1C :

Service life of actuating cylinder fittings used for attachment of cylinder to hinge arm is restricted to 1000 landings.

PN of fittings involved : C 61637  
C 61637-1  
C 61637-3  
C 61638  
C 61638-1

Reference : AIRBUS INDUSTRIE Service Bulletin N° A300-05-002.

This limited service life must be specified in chapter 5 of Airbus Industrie.

---

NOTA :The arrangements called for in this AD are covered in FRG by the LUFTTUCHTIGKEITSANWEISUNG (LBA) N° 75-281.

---

**EFFECTIVE : DECEMBER 31, 1975**

td/K

December 23,1975

AIRBUS INDUSTRIE  
A300 aircraft

75-223-3