GSAC

AIRWORTHINESS DIRECTIVE

released by DIRECTION GENERALE DE L'AVIATION CIVILE

Inspection and/or modifications described below are mandatory. No person may operate a product to which this Airworthiness Directive applies except in accordance with the requirements of this Airworthiness Directive.

Translation of 'Consigne de Navigabilité' ref. : 96-169-081(B) In case of any difficulty, reference should be made to the French original issue.

AIRBUS INDUSTRIE

A320 and A321 Aircraft

Activation of the spoiler function "phased lift dumping" (PLD)

This Airworthiness Directive applies to AIRBUS INDUSTRIE aircraft models A320-111, A320-211, A320-212, A320-231, A320-232, A321-111, A321-112 and A321-131, without AIRBUS INDUSTRIE modification n° 24745 or AIRBUS INDUSTRIE Service Bulletin A320-27-1088.

In order to reduce the possible delay in activation of automatic deceleration means in case of landing with strong cross wind and/or on contaminated runway, the following action is rendered mandatory on the effective date of this Airworthiness Directive:

- Within 12 months, activate the "phased lift dumping" function as per the instructions given in AIRBUS INDUSTRIE Service Bulletin A320-27-1088.

Ref.: AIRBUS INDUSTRIE Service Bulletin A320-27-1088

(or any further approved revision)

EFFECTIVE DATE: SEPTEMBER 07, 1996

d/JYR

August 28, 1996 AIRBUS INDUSTRIE
A320 and A321 Aircraft

96-169-081(B)